

AMENDMENTS TO THE SPECIFICATION

Please replace paragraph [0012] with the following amended paragraph:

[0012] Referring to FIG. 2, the valve assembly 30 consists of protrusions 32a and 32b formed inside the upper and lower pipes 26 and 28, respectively, a pair of check valves 34a and 34b and a ~~par~~ pair of solenoid valves 36a and 36b.

Please replace paragraph [0017] with the following amended paragraph:

[0017] Thereafter, once a pair of the solenoid valves [[6a]] 36a and 36b are driven, the check valves 34a and 34b move downward by the magnetic forces to open the upper and lower pipes 26 and 28, respectively. Hence, the water is supplied to the top and bottom nozzles 12 and 14 via the upper and lower pipes 26 and 28, respectively.

Please replace paragraph [0058] with the following amended paragraph:

[0058] And a ~~first~~ first step 91 is formed on an upper inside of the guide 85 to prevent the ball 87 lying at the inlet hole 82a from moving toward the third passage [[92]] 96 by a pressure of the water.

Please replace paragraph [0059] with the following amended paragraph:

[0059] Moreover, a second step 93 preventing the ball 87 lying at a lower side of the first outlet hole 84a from moving to the inlet hole 84a along the first passage 92 and a third step 95 preventing the ball lying at a lower side of the second outlet hole 84b from moving along the second passage 94 to the first outlet hole 84a are formed on a lower inside of the guide 85.